

THE MOST EFFICIENT EPA-Certified Stick Wood Burning Appliances*

Keep your house as warm as you want and eliminate your oil, gas or electric heat bill.



**CLASSIC
EDGE™**
TITANIUM HDX
Outdoor Wood Furnaces

The Classic Edge HDX outdoor wood furnace is easy to operate and maintain. Models to match many installation scenarios are available.

- **Value AND performance** - the revolutionary patent-pending design of the Classic Edge Titanium HDX combines value and performance without sacrificing Central Boiler quality, reliability and performance.
- **Up to 60% less wood** - compared to traditional and some other methods of wood heating.
- **Stainless steel firebox** - constructed of titanium-enhanced stainless steel, the inside of the firebox is impervious to corrosion and provides excellent heat transfer performance.
- **Easy to maintain** - firebox design and heat exchanger system make for easy maintenance and cleaning.

- **Easy to operate** - FireStar combustion controller takes the guesswork out of operating.
- **It's better in the app** - With live monitoring, performance history, a Message Center and Quick Access tools, the Central Boiler Connect app is the best way to stay in touch with your outdoor furnace when it is connected to Wi-Fi. Available on iOS and Android.



12-Month Same-As-Cash¹ or **9.99% 5 Year Loan²** or **Traditional Loan³ As low as 8.99% APR**

See back page for financing details and other important information.

Central
FINANCING™
Payments as low as³
\$138/mo



CLASSIC EDGE 360
TITANIUM HDX

Overall Efficiency (LHV) - 88.4%*
Overall Efficiency (HHV) - 82.2%*
Mfr's Rated Heat Output Capacity -
150,000 Btu/hr
Heat Output (12 hr) - 66,894 Btu/hr

EPA Certified for residential use
Firebox Volume - 10 cubic ft
Firebox Dimensions - 28"L x 29"H x 21"W
Door - 16"W x 16"H
Ash Cleanout Door - 18"W x 9"H
Water Capacity - 150 gal.
Weight - 1,365 lbs
One set of 1-1/4" Supply and Return Ports**
**Can be configured for two pumps.

Furnace Options and Accessories:

- LED Light Kits
- Pump Panel Extension Kit



CLASSIC EDGE 560
TITANIUM HDX

Overall Efficiency (LHV) - 86.4%*
Overall Efficiency (HHV) - 80.6%*
Mfr's Rated Heat Output Capacity -
190,000 Btu/hr
Heat Output (12 hr) - 92,000 Btu/hr

EPA Certified for residential use
Firebox Volume - 14 cubic ft
Firebox Dimensions - 33"L x 32"H x 23"W
Door - 18"W x 18"H
Ash Cleanout Door - 18"W x 9"H
Water Capacity - 205 gal.
Weight - 1,668 lbs
One set of 1-1/4" Supply and Return Ports**
**Can be configured for two pumps.
Bypass Door and Alarm

Furnace Options and Accessories:

- LED Light Kits
- Pump Panel Extension Kit



CLASSIC EDGE 865
TITANIUM HDX

Overall Efficiency (LHV) - 92.7%*
Overall Efficiency (HHV) - 86.5%*
Mfr's Rated Heat Output Capacity -
245,000 Btu/hr
Heat Output (12 hr) - 156,000 Btu/hr

EPA Certified for residential use
Firebox Volume - 23 cubic ft
Firebox Dimensions - 37"L x 41.5"H x 26"W
Door - 22.75"W x 28.75"H
Ash Cleanout Door - 19"W x 11"H
Water Capacity - 360 gal.
Weight - 2,500 lbs
Three sets of 1-1/4" Supply and Return Ports
Bypass Door and Alarm

Furnace Options and Accessories:

- LED Light Kits



CLASSIC EDGE 960
TITANIUM HDX

Overall Efficiency (LHV) - 92.1%*
Overall Efficiency (HHV) - 85.6%*
Mfr's Rated Heat Output Capacity -
400,000 Btu/hr
Heat Output (12 hr) - 212,957 Btu/hr

EPA Certified for residential use
Firebox Volume - 32 cubic ft
Firebox Dimensions - 42.75"L x 43.5"H x 31.5"W
Door - 22.75"W x 28.75"H
Ash Cleanout Door - 20"W x 11"H
Water Capacity - 420 gal.
Weight - 2,714 lbs
One set of 1-1/4" Supply and Return Ports
Two sets of 3/4" Supply and Return Ports
Bypass Door and Alarm

Furnace Options and Accessories:

- LED Light Kits

*Test efficiencies are available on Central Boiler website. Classic Edge HDX models are U.S. EPA Step 2 Certified.

As the outdoor wood furnace that set the standard for quality and revolutionized the industry, the Classic is the perfect choice for heating your business, shop, barn and more. Check with your local Central Boiler dealer today.

In the U.S., the Classic is for non-residential applications only.

CLASSIC™ TITANIUM

CENTRAL BOILER CLASSIC[®] XC Outdoor Coal Furnace

The Classic XC outdoor coal furnace delivers unmatched value, legendary reliability and low-maintenance operation.

CENTRAL BOILER CLASSIC[®] X Outdoor Wood Furnace



Classic X 6048

Door 23" x 31"
Firebox 59" x 44" x 36"
Firebox Volume 37.7 cu ft
Weight (est.) 2,000 lbs
Water Capacity 350 gal.
Chimney One 4-foot 8" section
1-1/4" Supply/Return Ports 3 ea

Classic X 5036

Door 23" x 23"
Firebox 50" x 34" x 30"
Firebox Volume 20.6 cu ft
Weight (est.) 1,300 lbs
Water Capacity 171 gal.
Chimney One 4-foot 6" section
1-1/4" Supply/Return Ports 2 ea

Credit and loans provided by Regions Bank, Member FDIC, (650 S. Main St., Suite 1000, Salt Lake City, UT 84101) on approved credit, for a limited time. ¹19.99% fixed APR (provided however, APR will not exceed 15.99% for residents of New Jersey and 17.99% for residents of Florida and Wisconsin), effective as of March 2026, subject to change. Minimum loan amounts apply. Interest starts accruing when funds are disbursed. Interest waived if repaid in 365 days from first disbursement. When open line period ends, the balance becomes a fixed rate installment loan; repayment terms vary from 24 to 132 months. Actual loan term may be shorter if less than the full approved amount of credit is used. First monthly loan payment due 365 days after first disbursement. If no payments made during same-as-cash period and APR of 19.99%, monthly payments vary from \$21.99 to \$30.82 per \$1,000 borrowed depending on term. The minimum monthly payment will be no less than \$50.00. ²9.99% fixed APR, subject to change. Minimum loan amounts apply. Interest starts accruing when funds are disbursed. Open line period payments due 90 days after origination and monthly thereafter during open line period. When open line period ends, the balance becomes a fixed rate installment loan; repayment term is 60 months. Actual loan term may be shorter if less than the full approved amount of credit is used. First monthly loan payment due 30 days from the end of the open line period. 60 monthly payments of \$21.69 per \$1,000 borrowed. The minimum monthly payment will be no less than \$50.00. ³8.99% to 24.49% fixed APR (provided however, APR will not exceed 15.99% for residents of New Jersey and 17.99% for residents of Florida and Wisconsin), subject to change. Minimum loan amounts apply. Interest starts accruing when funds are disbursed. Open line period payments due 90 days after origination and monthly thereafter during open line period. When open line period ends, the balance becomes a fixed rate installment loan; repayment terms vary from 12 to 144 months. Actual loan term may be shorter if less than the full approved amount of credit is used. First monthly loan payment due 30 days from the end of the open line period. Monthly payments vary from \$11.49 to \$30.27 per \$1,000 borrowed depending on term and interest rate. The minimum monthly payment will be no less than \$50.00. \$138/mo payment shown for Classic Edge 360 Titanium HDX. \$110/mo payment shown for Classic CL4030 Titanium. \$146/mo payment shown for Maxim M255PE.



CL 6048

Heat Transfer Area - 119 sq ft
Door - 23"W x 31"H
Firebox - 60"L x 48"H x 36"W
Water Capacity - 393 gal.
Weight - 2,140 lbs



CL 7260

Heat Transfer Area - 179 sq ft
Door - 30"W x 40"H
Firebox - 72"L x 60"H x 40"W
Water Capacity - 764 gal.
Weight - 3,336 lbs



CL 5036

Heat Transfer Area - 74 sq ft
Door - 23"W x 23"H
Firebox - 50"L x 36"H x 30"W
Water Capacity - 196 gal.
Weight - 1,492 lbs



CL 4030

Heat Transfer Area - 52 sq ft
Door - 20"W x 20"H
Firebox - 40"L x 30"H x 26"W
Water Capacity - 140 gal.
Weight - 1,140 lbs

Central
FINANCING™
Payments as low as⁴
\$110/mo

12-Month or **9.99%** or **Traditional Loan³**
Same-As-Cash¹ or 5 Year Loan² or As low as 8.99% APR

See back page for financing details and other important information.



Central
FINANCING™

Payments as low as⁵
\$149/mo

Available in Two Sizes:

Classic XC 6048

Door 23" x 31"
Firebox 59" x 44" x 36"
Firebox Volume 37.7 cu ft
Weight (est.) 2,000 lbs
Water Capacity 350 gal.
Chimney One 4-foot 8" section
1-1/4" Supply/Return Ports 3 ea

Classic XC 5036

Door 23" x 23"
Firebox 50" x 34" x 30"
Firebox Volume 20.6 cu ft
Weight (est.) 1,300 lbs
Water Capacity 171 gal.
Chimney One 4-foot 6" section
1-1/4" Supply/Return Ports 2 ea

The use of wood in this furnace, except for coal ignition purposes, is prohibited by law in the U.S.



CentralBoiler.com