

THE MOST EFFICIENT EPA-Certified Stick Wood Burning Appliances*

Keep your house as warm as you want and eliminate your oil, gas or electric heat bill.



**CLASSIC
EDGE™**
TITANIUM HDX
Outdoor Wood Furnaces

The Classic Edge HDX outdoor wood furnace is easy to operate and maintain. Models to match many installation scenarios are available.

- **Value AND performance** - the revolutionary patent-pending design of the Classic Edge Titanium HDX combines value and performance without sacrificing Central Boiler quality, reliability and performance.
- **Up to 60% less wood** - compared to traditional and some other methods of wood heating.
- **Stainless steel firebox** - constructed of titanium-enhanced stainless steel, the inside of the firebox is impervious to corrosion and provides excellent heat transfer performance.
- **Easy to maintain** - firebox design and heat exchanger system make for easy maintenance and cleaning.

- **Easy to operate** - FireStar combustion controller takes the guesswork out of operating.
- **It's better in the app** - With live monitoring, performance history, a Message Center and Quick Access tools, the Central Boiler Connect app is the best way to stay in touch with your outdoor furnace when it is connected to Wi-Fi. Available on iOS and Android.



CLASSIC EDGE 360
TITANIUM HDX

Overall Efficiency (LHV) - 88.4%*
Overall Efficiency (HHV) - 82.2%*
Mfr's Rated Heat Output Capacity -
150,000 Btu/hr
Heat Output (12 hr) - 66,894 Btu/hr

EPA Certified for residential use
Firebox Volume - 10 cubic ft
Firebox Dimensions - 28"L x 29"H x 21"W
Door - 16"W x 16"H
Ash Cleanout Door - 18"W x 9"H
Water Capacity - 150 gal.
Weight - 1,365 lbs
One set of 1-1/4" Supply and Return Ports**
**Can be configured for two pumps.

Furnace Options and Accessories:
• LED Light Kits
• Pump Panel Extension Kit



CLASSIC EDGE 560
TITANIUM HDX

Overall Efficiency (LHV) - 86.4%*
Overall Efficiency (HHV) - 80.6%*
Mfr's Rated Heat Output Capacity -
190,000 Btu/hr
Heat Output (12 hr) - 92,000 Btu/hr

EPA Certified for residential use
Firebox Volume - 14 cubic ft
Firebox Dimensions - 33"L x 32"H x 23"W
Door - 18"W x 18"H
Ash Cleanout Door - 18"W x 9"H
Water Capacity - 205 gal.
Weight - 1,668 lbs
One set of 1-1/4" Supply and Return Ports**
**Can be configured for two pumps.
Bypass Door and Alarm

Furnace Options and Accessories:
• LED Light Kits
• Pump Panel Extension Kit



CLASSIC EDGE 865
TITANIUM HDX

Overall Efficiency (LHV) - 92.7%*
Overall Efficiency (HHV) - 86.5%*
Mfr's Rated Heat Output Capacity -
245,000 Btu/hr
Heat Output (12 hr) - 156,000 Btu/hr

EPA Certified for residential use
Firebox Volume - 23 cubic ft
Firebox Dimensions - 37"L x 41.5"H x 26"W
Door - 22.75"W x 28.75"H
Ash Cleanout Door - 19"W x 11"H
Water Capacity - 360 gal.
Weight - 2,500 lbs
Three sets of 1-1/4" Supply and Return Ports
Bypass Door and Alarm

Furnace Options and Accessories:
• LED Light Kits



CLASSIC EDGE 960
TITANIUM HDX

Overall Efficiency (LHV) - 92.1%*
Overall Efficiency (HHV) - 85.6%*
Mfr's Rated Heat Output Capacity -
400,000 Btu/hr
Heat Output (12 hr) - 212,957 Btu/hr

EPA Certified for residential use
Firebox Volume - 32 cubic ft
Firebox Dimensions - 42.75"L x 43.5"H x 31.5"W
Door - 22.75"W x 28.75"H
Ash Cleanout Door - 20"W x 11"H
Water Capacity - 420 gal.
Weight - 2,714 lbs
One set of 1-1/4" Supply and Return Ports
Two sets of 3/4" Supply and Return Ports
Bypass Door and Alarm

Furnace Options and Accessories:
• LED Light Kits

*Test efficiencies are available on Central Boiler website. Classic Edge HDX models are U.S. EPA Step 2 Certified.

As the outdoor wood furnace that set the standard for quality and revolutionized the industry, the Classic is the perfect choice for heating your business, shop, barn and more. Check with your local Central Boiler dealer today.

In the U.S., the Classic is for non-residential applications only.

CLASSIC™ TITANIUM

CENTRAL BOILER CLASSIC^{XC} Outdoor Coal Furnace

The Classic XC outdoor coal furnace delivers unmatched value, legendary reliability and low-maintenance operation.

CENTRAL BOILER CLASSIC^X Outdoor Wood Furnace



Classic X 6048

Door 23" x 31"
Firebox 59" x 44" x 36"
Firebox Volume 37.7 cu ft
Weight (est.) 2,000 lbs
Water Capacity 350 gal.
Chimney One 4-foot 8" section
1-1/4" Supply/Return Ports 3 ea

Classic X 5036

Door 23" x 23"
Firebox 50" x 34" x 30"
Firebox Volume 20.6 cu ft
Weight (est.) 1,300 lbs
Water Capacity 171 gal.
Chimney One 4-foot 6" section
1-1/4" Supply/Return Ports 2 ea



CL 6048

Heat Transfer Area - 119 sq ft
Door - 23"W x 31"H
Firebox - 60"L x 48"H x 36"W
Water Capacity - 393 gal.
Weight - 2,140 lbs



CL 7260

Heat Transfer Area - 179 sq ft
Door - 30"W x 40"H
Firebox - 72"L x 60"H x 40"W
Water Capacity - 764 gal.
Weight - 3,336 lbs



CL 5036

Heat Transfer Area - 74 sq ft
Door - 23"W x 23"H
Firebox - 50"L x 36"H x 30"W
Water Capacity - 196 gal.
Weight - 1,492 lbs



CL 4030

Heat Transfer Area - 52 sq ft
Door - 20"W x 20"H
Firebox - 40"L x 30"H x 26"W
Water Capacity - 140 gal.
Weight - 1,140 lbs



Available in Two Sizes:

Classic XC 6048

Door 23" x 31"
Firebox 59" x 44" x 36"
Firebox Volume 37.7 cu ft
Weight (est.) 2,000 lbs
Water Capacity 350 gal.
Chimney One 4-foot 8" section
1-1/4" Supply/Return Ports 3 ea

Classic XC 5036

Door 23" x 23"
Firebox 50" x 34" x 30"
Firebox Volume 20.6 cu ft
Weight (est.) 1,300 lbs
Water Capacity 171 gal.
Chimney One 4-foot 6" section
1-1/4" Supply/Return Ports 2 ea

The use of wood in this furnace, except for coal ignition purposes, is prohibited by law in the U.S.

